

PRODUCT SPECIFICATIONS

Sunstar Classic Hybrid is a waterproof product with high definition print and anti-microbial surface. Designed for family living.

AVAILABLE CLASSIC HYBRID RANGE	TEST DATA – CLASSIC HYBRID																																
Classic – 1530x183x5.5mm	<table border="1"> <thead> <tr> <th colspan="2">TEST DATA – CLASSIC HYBRID</th> </tr> </thead> <tbody> <tr> <td>Scratch Resistance</td> <td>AC3</td> </tr> <tr> <td>Reaction to fire tests</td> <td></td> </tr> <tr> <td>- CHF Value</td> <td>8.6 kW/m2 Mean</td> </tr> <tr> <td>- Smoke Value</td> <td>90.4% Mean</td> </tr> <tr> <td>Charring</td> <td>Yes</td> </tr> <tr> <td>Slip Resistance Classification</td> <td></td> </tr> <tr> <td>Wet pendulum</td> <td>P3</td> </tr> <tr> <td>Emission Test ASTM</td> <td></td> </tr> <tr> <td>D5116-2017</td> <td></td> </tr> <tr> <td>VOC</td> <td>Pass</td> </tr> <tr> <td>Formaldehyde</td> <td>Pass</td> </tr> <tr> <td>Acoustic Laboratory Measurement</td> <td></td> </tr> <tr> <td>57dB</td> <td>Pass</td> </tr> <tr> <td>Acoustic Star Rating Assessment</td> <td></td> </tr> <tr> <td>Typical residential built form</td> <td>5 Star</td> </tr> </tbody> </table>	TEST DATA – CLASSIC HYBRID		Scratch Resistance	AC3	Reaction to fire tests		- CHF Value	8.6 kW/m2 Mean	- Smoke Value	90.4% Mean	Charring	Yes	Slip Resistance Classification		Wet pendulum	P3	Emission Test ASTM		D5116-2017		VOC	Pass	Formaldehyde	Pass	Acoustic Laboratory Measurement		57dB	Pass	Acoustic Star Rating Assessment		Typical residential built form	5 Star
TEST DATA – CLASSIC HYBRID																																	
Scratch Resistance	AC3																																
Reaction to fire tests																																	
- CHF Value	8.6 kW/m2 Mean																																
- Smoke Value	90.4% Mean																																
Charring	Yes																																
Slip Resistance Classification																																	
Wet pendulum	P3																																
Emission Test ASTM																																	
D5116-2017																																	
VOC	Pass																																
Formaldehyde	Pass																																
Acoustic Laboratory Measurement																																	
57dB	Pass																																
Acoustic Star Rating Assessment																																	
Typical residential built form	5 Star																																
<table border="1"> <thead> <tr> <th>CLASSIC HYBRID</th> </tr> </thead> <tbody> <tr> <td>Underlay Integrated IXPE Underlay</td> </tr> <tr> <td>Core Multi-layer SPC: Stone polymer composite core PVC: Virgin Stone: Non-crystalline silica carbonate</td> </tr> <tr> <td>Wear Layer Thickness: 0.5mm Finish: Embossed Matte Ceramic Coating Treatment: +ion Charged Antimicrobial</td> </tr> <tr> <td>Joins Joint System: Unilin Click Edge Treatment: Micro Bevel</td> </tr> </tbody> </table>	CLASSIC HYBRID	Underlay Integrated IXPE Underlay	Core Multi-layer SPC: Stone polymer composite core PVC: Virgin Stone: Non-crystalline silica carbonate	Wear Layer Thickness: 0.5mm Finish: Embossed Matte Ceramic Coating Treatment: +ion Charged Antimicrobial	Joins Joint System: Unilin Click Edge Treatment: Micro Bevel																												
CLASSIC HYBRID																																	
Underlay Integrated IXPE Underlay																																	
Core Multi-layer SPC: Stone polymer composite core PVC: Virgin Stone: Non-crystalline silica carbonate																																	
Wear Layer Thickness: 0.5mm Finish: Embossed Matte Ceramic Coating Treatment: +ion Charged Antimicrobial																																	
Joins Joint System: Unilin Click Edge Treatment: Micro Bevel																																	

WARRANTY



Limited
Lifetime
Residential
Warranty



Commercial
10 Year Wear
Warranty



Lifetime
Structural
Warranty



Classic Hybrid
HQ Wood Pty Ltd TA Sunstar Timber Flooring
Phone 1300 081 999 Email info@sunstarflooring.com.au