

PRODUCT SPECIFICATIONS

Sunstar Classic Oak engineered timber is manufactured with an 8 layer multi-ply eucalyptus core, making it suitable for direct stick or floating floor installation.

AVAILABLE CLASSIC OAK RANGES
Classic – 1900x190x14/2mm
Builders – 1900x190x12/1.2mm
Wide Board – 1900x220x14/2mm
Herringbone – 600x120x14/2mm

CLASSIC OAK (CLASSIC, BUILDERS COMMERCIAL, WIDE, HERRINGBONE)
<p>Product Grading Natural timber colour variation Log Grade: Quota Logs Knots: Allowable if unbroken, max. 40mm Ingrown Bark: Not allowed Filled Defects: Colour may vary Sapwood: Max 10% boards / Max 10% width End checks: Not allowed Insect Damage: Not allowed Timber origin: Europe (FSC Approved)</p> <p>Wear Layer Thickness: 1.2mm, 2mm, 3mm Finish: Brushed matte UV Coating 8 layer</p> <p>Joins Joint System: Droplock / T&G Left & Right (Herringbone) Join Treatment: Waxed Click System (T&G Untreated) Edge Treatment: Micro Bevel</p>

TEST DATA – CLASSIC OAK (CLASSIC, WIDE, HERRINGBONE)	
Reaction to fire tests	
- CHF Value	3.1 KW/m ² Mean
- HF-30 Value	3.4 KW/m ² Mean
- Smoke Value	16 %.min Mean
Blistering	Yes
Penetration of flame through to substrate	Yes
Slip Resistance Classification	
Wet pendulum	P3
Emission Test ASTM	
D5116-2017	
VOC Green Star	Pass
Formaldehyde Green Star	Pass
Acoustic Laboratory Measurement	
61dB	Pass
Acoustic Star Rating Assessment	
Typical residential built form	5 Star

TEST DATA – CLASSIC OAK (BUILDERS)	
Reaction to fire tests	
- CHF Value	5.6 KW/m ² Mean
- HF-30 Value	5.1 KW/m ² Mean
- Smoke Value	27 %.min Mean
Blistering	Yes
Penetration of flame through to substrate	Yes
Slip Resistance Classification	
Wet pendulum	P3
Emission Test ASTM	
D5116-2017	
VOC Green Star	Pass
Formaldehyde Green Star	Pass
Acoustic Laboratory Measurement	
61dB	Pass
Acoustic Star Rating Assessment	
Typical residential built form	5 Star

WARRANTY



Residential
20 Year Wear
Warranty



Commercial
5 Year Wear
Warranty



Lifetime
Structural
Warranty



Classic Oak
 HQ Wood Pty Ltd TA Sunstar Timber Flooring
 Phone 1300 081 999 Email info@sunstarflooring.com.au